

## Product Specifications

<b>G3 Series/ Lithium-Ion Forklifts</b>				
<b>Model</b>		<b>CPD40</b>	<b>CPD45</b>	<b>CPD50</b>
<b>Loading capacity</b>	lbs	8000	9000	11000
<b>Load center</b>	in	20	20	20
<b>Operating type</b>		Seated Forklift	Seated Forklift	Seated Forklift
<b>Wheels type</b>		Solid (S)	Solid (S)	Solid (S)
<b>Overall height (with overhead)</b>	in	90	90	90
<b>Max. lifting height</b>	in	185	185	185
<b>Overall length (with fork/without fork)</b>	in			
<b>Overall width</b>	in	53	53	59
<b>Min. turning radius</b>	in	101	101	101
<b>Travel speed (laden/unladen)</b>	mph	8/8.7	8/8.7	8/8.7
<b>Battery voltage/ rated capacity (5h)</b>	v/ah	80/542	80/606	80/606
<b>Drive motor - 60 min. rating</b>	hp	26.8	26.8	26.8
<b>Pump motor - 15 min. rating</b>	hp	35.5	35.5	35.5
<b>Drive motor control method</b>		MOSFET/AC	MOSFET/AC	MOSFET/AC
<b>Controls</b>		ZAPI	ZAPI	ZAPI
<b>Tire size (front/rear)</b>	in	250-15/ 21×8-9	250-15/ 21×8-9	28×12.5-15/ 21×8-9
<b>Total weight (with/without battery)</b>	lbs	14700/13415	15068/13558	15895/14385