

Product Specifications

H3 Series/ LP Pneumatic Forklifts								
Model		CPYD10	CPYD15	CPYD18	CPYD20	CPYD25	CPYD30	CPYD35
Loading capacity	lbs	2000	3000	3500	4000	5000	6000	7000
Load center	in	24						
Operating type		Seated Forklift						
Wheels type		Polyurethane (PU)						
Overall height (with overhead)	in	84	84	84	84.6	84.6	85.4	85.4
Max. lifting height	in	185						
Overall length (with fork/without fork)	in	125.9/89.6	126/89.8	126.7/90.5	137.8/101.6	143.9/101.6	150.3/108.2	151.0/108.9
Overall width	in	42.1	42.1	42.1	45.3	45.3	48.2	48.2
Min. turning radius	in	73.8	75.2	76	85.4	88.2	94.5	95.3
Travel speed (laden/unladen)	mph	10.0/10.6	10.0/10.6	10.0/10.6	11.2/11.8	11.2/11.8	11.8/11.8	11.8/11.8
Engine type	mph	Kubota WG2503						
Engine rated power	hp/rpm	GAS:57.4/2600 LPG:58.3/2600						
Engine rated torque	(ft*lb)/rpm	GAS:128.7/1400 LPG:120.7/1800						
Tire size (front/rear)	in	6.50-10-10PR/5.00-8-8PR			7.00-12-12PR/ 6.00-9-10PR	7.00-12-12PR/ 6.00-9-10PR	28×9-15-12PR/ 6.50-10-10PR	28×9-15-14PR/ 6.50-10-10PR
Total weight	lbs	5414	6079	6365	7665	8370	9692	11013